

**MAX**

***SuperLocator***  
**SN438J**

**ENGINEERED FOR  
PERFORMANCE**

**METAL CONNECTOR NAILER UP TO 1-1/2"**



**METAL  
CONNECTOR NAILER**

**80** YEAR  
ANNIVERSARY

**MAX****ENGINEERED FOR PERFORMANCE****SuperLocator**  
**SN438J**

## TOOL FEATURES

### 1 MAINTENANCE FREE END CAP FILTER

The patented, self-cleaning maintenance-free end cap filter captures foreign substances before they can enter the tool and automatically ejects them when the air hose is disconnected.

### 2 HEAVY DUTY RAFTER HOOK

The heavy duty adjustable rafter hook rotates 270° and allows the tool to be hung on rafters and joists when it is not in use.

### 3 PRECISION PLACEMENT NOSE

The nose design exposes the nail tip to allow the precise placement of fasteners into connector holes.

### 4 EASY TWIST AIR DEFLECTOR

Air deflector cap rotates 360° to divert exhaust air away from the user.

### 5 ANTI-DRY FIRE MECHANISM

The tool automatically stops operation when the nail level is low to prevent dry fires.

### 6 ANTI-DOUBLE FIRE NOSE

An extruded metal tip prevents a 2nd nail from accidentally being shot when the 1st nail is firmly pressed against the wood surface.

### 7 BEEFED UP CONTACT ARM

Thicker contact arm provides greater protection from breakage due to nail jams and accidental dropping of the tool.

### 8 HEAVY DUTY DRIVER BLADE

A denser driver blade provides 1.7 times more durability than competitive tools.



## TOOL SPECIFICATIONS

Weight	5.0 lbs
H x W x L	10-7/16" x 4-3/16" x 12-13/32"
Loading Capacity	32 nails
Operating Pressure	70 to 100 psi
Air Consumption	0.069 ft3 at 90 psi

## FASTENER SPECIFICATIONS

Nail Length	1-1/2"
Shank Diameter	.131" / .148"
Shank Type	Smooth
Head Diameter	.280"
Collation Angle	34 degree paper collation

## APPLICATIONS ▶▶

Strapping Joist Hangers Hurricane Ties Rafter Ties/Connectors  
Post Bases and Cap Foundation Anchors & Holdowns

**MAX****MAX USA CORP.**

205 Express St, Plainview NY 11803

800-223-4293

www.maxusacorp.com

DEALER: